

ACETONE

SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	ACETONE	53 ASSEMBLY DRIVE
Manufacturers Code:	ACE1, ACE5, ACE25	TULLAMARINE VIC 3043
Date:	September 2020	ABN: 40 959 725 049 Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598 Email: gsmart@bigpond.net.au Web: www.quicksmartproducts.com.au

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name	ACETONE
Company Name	QUICK SMART PRODUCTS
Address	53 Assembly Drive Tullamarine Vic 3043
Telephone	(03) 9338 6655 (BH) Poisons Information Centre 131126 (AH) (03) 9336 7945 (AH)
Recommended Use	Solvent, cleansing product

2. HAZARDS IDENTIFICATION

Statement of Hazardous Nature Classified as **Hazardous** according to the criteria of the Australian Safety and Compensation Council ASCC (formerly NOHSC) Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008] 3rd Edition.

Acetone is **classified** as **Dangerous** Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

GHS Classification

Hazard Categories

Flammable Liquids: Category 2
Serious Eye Damage/Irritation: Category 2A
Target Organ Systematic Toxicant - Single Exposure: Category 3

GHS Label Elements

Signal Word

DANGER

Symbol(s)



Hazard Statements

H225: Flammable liquid and vapour
H319: Causes serious eye irritation
H336: May cause drowsiness and dizziness

Precautionary Statements

Prevention

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233: Keep container tightly closed
P235: Keep cool
P240: Ground/bond container and receiving equipment
P241: Use explosion-proof electrical/ventilation/lighting equipment
P242: Use only non-sparking tools
P243: Take precautionary measures against static discharge
P261: Avoid breathing mist, vapours, spray
P264: Wash thoroughly after handling
P271: Use only outdoors or in a well-ventilated area
P273: Avoid release to the environment
P280: Wear protective gloves/eye protection/face protection
P281: Use personal protective equipment as required.

ACETONE

SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	ACETONE	53 ASSEMBLY DRIVE
Manufacturers Code:	ACE1, ACE5, ACE25	TULLAMARINE VIC 3043
Date:	September 2020	ABN: 40 959 725 049
		Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598
		Email: gsmart@bigpond.net.au
		Web: www.quicksmartproducts.com.au

Response	P303+P361+P353: If ON SKIN (or hair): Take off contaminated clothing and wash before reuse. Rinse skin with water/shower
	P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
	P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
	P312: Call a POISON CENTER or doctor/physician if you feel unwell
	P321: Specific treatment (see details on label)
	P322: Specific measures (see details on this label)
	P331: Do NOT induce vomiting
	P332+P313: If skin irritation occurs: Get medical advice/attention
	P337+P313: If eye irritation persists: Get medical advice/attention
	P362: Take off contaminated clothing and wash before reuse
	P363: Wash contaminated clothing before reuse
	P370+P378: In case of fire: Use appropriate media for extinction
Disposal	P501: Dispose of contents and container to appropriate waste site of reclaimer in accordance with local and national regulations
EC Hazards	EUH066: Repeated exposure may cause skin dryness or cracking.

Other Hazards which do not result in classification

None

3. COMPOSITION / INFORMATION ON INGREDIENTS

Classification of Components According to GHS

Chemical Name	CAS No.	Hazard Class	Hazard Statement	Concentration
Acetone	67-64-1	Flam. Liq., 3 Eye irrit. 2A STOT SE., 3	H225 H319 H336	>99.0% W

4. FIRST AID MEASURES

Information

Consult a physician. Show this safety data sheet to the doctor in attendance.

Ingestion	DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
Eyes	Immediately flush eyes with large amounts of water for at least 15minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.
Skin	Remove contaminated clothing; wash off with plenty of water and soap. Consult a physician if any symptoms arise.
Inhaled	Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
First Aid Facilities	Eye wash fountains and safety showers should be available for emergency use.
Advice to Doctor	The most important known symptoms and effects are described in the labelling and in section 11.

Most Important Symptoms and Effects Acute and Delayed

Cough, nausea, vomiting, headache, unconsciousness, shortness of breath, dizziness, narcosis.

ACETONE

SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	ACETONE	53 ASSEMBLY DRIVE
Manufacturers Code:	ACE1, ACE5, ACE25	TULLAMARINE VIC 3043
Date:	September 2020	ABN: 40 959 725 049 Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598 Email: gsmart@bigpond.net.au Web: www.quicksmartproducts.com.au

Immediate Medical Attention, Special Treatment

Lung oedema, central nervous system effects, Prolonged skin contact may degrease the skin and produce dermatitis.

5. FIRE FIGHTING MEASURES

Specific Hazards	Under conditions giving incomplete combustion, hazardous gases produced may consist of: carbon monoxide (CO) carbon dioxide (CO ₂) Combustion gases of organic materials must in principle be graded as inhalation poisons. Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback. Vapours may form explosive mixtures with air.
Suitable Extinguishing Media	Preferably: alcohol resistant foam, water spray, polyvalent foam, BC powder, carbon dioxide.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.
Special Protective Precautions and Equipment for Fire Fighters	Wear full protective clothing and self-contained breathing apparatus.
Other Advice	Cool containers / tanks with water spray. Dike and collect water used to fight fire. Water run-off can cause environmental damage. Keep people away from and upwind of fire.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of the Safety Data Sheet.

Personal Precautions, Protective Equipment and Emergency Procedures	Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.
Environmental Procedures	Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
Methods and Materials for Containment and Cleaning Up	Contain spillage and then collect with an electrically protected vacuum cleaner or by wet brushing and place in container for disposal according to local regulations (see section 13).
Additional Advice	Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. The vapour is heavier than air, spreads along the ground and distant ignition is possible. See Chapter 13 for information on disposal. For guidance on selection of personal protective equipment see chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see chapter 13 of this Safety Data Sheet.

ACETONE

SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	ACETONE	53 ASSEMBLY DRIVE
Manufacturers Code:	ACE1, ACE5, ACE25	TULLAMARINE VIC 3043
Date:	September 2020	ABN: 40 959 725 049
		Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598
		Email: gsmart@bigpond.net.au
		Web: www.quicksmartproducts.com.au

7. HANDLING AND STORAGE

Precautions for Safe Handling	Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. Refer to guidance under handling section.
Conditions for Safe Storage, Including any Incompatibilities	Store in a well-ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidants.
Unsuitable Material	Synthetic material.
Incompatible Material	Oxidizing agents, reducing agents, (strong) acids, (strong) bases, halogens and amines.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Occupational Exposure Limits

Material	Type	ppm	mg/m ³
Acetone	STEL	750	2400
Acetone	TWA	500	1800

Biological Exposure Index (BEI) No biological limit allocated.

Engineering Controls

Ventilation

Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 2430.3.1:1997 : Classification of hazardous areas - Examples of area classification - General, for further information concerning ventilation requirements.

Appropriate Engineering Controls

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Use sealed systems as far as possible. Firewater monitors and deluge systems are recommended. Eye washes and showers for emergency use.

Personal Protection

Hand Protection

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739, AS/NZS:2161) made from the following materials may provide suitable chemical protection: Longer term protection: Viton. Incidental contact/Splash protection: Nitrile rubber. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

ACETONE

SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	ACETONE	53 ASSEMBLY DRIVE
Manufacturers Code:	ACE1, ACE5, ACE25	TULLAMARINE VIC 3043
Date:	September 2020	ABN: 40 959 725 049
		Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598
		Email: gsmart@bigpond.net.au
		Web: www.quicksmartproducts.com.au

Eye Protection	Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Respiratory Protection	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for organic gases and vapours [Type A boiling point > 65°C (149°F)] meeting EN14387. Where respiratory protective equipment is required, use a full-face mask. Where air-filtering respirators are unsuitable (e.g., airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.
Body Protection	Chemical resistant gloves/gauntlets, boots, and apron. Where risk of splashing or in spillage clean up, use chemical resistant one-piece overall with integral hood. Wear antistatic and flame retardant clothing.
Smoking & Other Dusts	Smoking must be prohibited in all areas where this product is used - see safety information on flammability.
Thermal Hazards	Not applicable.
Monitoring Methods	Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapor.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Colourless clear liquid
Odour	Aromatic odour. Sweet odour. Fruity odour
Odour Threshold	306-653ppm (737-1574 mg/dm ³)
Molecular Weight	58.08g/mol
Solubility in Water	Soluble
Density	786 kg/m ³
Relative Density	0.79g/cm ³
pH Value	7
Relative Evaporation Rate (butyl acetate=1)	6
Relative Evaporation Rate (ether=1)	2
Melting Point	-95°C
Vapour Pressure	247 hPa at 20°C, 828 hPa at 50°C

ACETONE

SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043 ABN: 40 959 725 049 Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598 Email: gsmart@bigpond.net.au Web: www.quicksmartproducts.com.au
Product Name:	ACETONE	
Manufacturers Code:	ACE1, ACE5, ACE25	
Date:	September 2020	

Vapour Density	2.0 (Air=1) @ 20°C
Flash Point	-18°C
Auto Ignition Temp	465°C
Flammable Limits	UEL: 12.6% (V) LEL : 2.8% (V)
Boiling Point/Range	56°C @ 1013 hPa

10. STABILITY AND REACTIVITY

Chemical Stability	Unstable under exposure to light otherwise stable under normal conditions.
Incompatible Materials	Strong acids, strong bases.
Conditions to Avoid	Direct sunlight, heat, sparks, flame and build-up of static electricity.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Hazardous Reactions	Hazardous polymerization will not occur. Vapours may form explosive mixture with air.

11. TOXICOLOGICAL INFORMATION

LD50 Oral Rat	5800 mg/kg
LD50 Dermal Rabbit	20000 mg/kg
LC50 Inhalation Rat (mg/L)	71 mg/L/4hr
LC50 Inhalation Rat (ppm)	30000 ppm/L/4hr
Skin Corrosion/Irritation	Not classified.
Serious Eye Damage/Irritation	Causes serious eye irritation.
Germ Cell Mutagenicity	Not classified.
Reproductive Toxicity	Not classified.
Specific Target Organ Toxicity (Single Exposure)	May cause drowsiness or dizziness.
Specific Target Organ Toxicity (Repeated Exposure)	Not classified.
Aspiration Hazard	Not classified.
Potential Adverse Human Health Effects and Symptoms	Not classified.
Symptoms/Injuries after Inhalation	EXPOSURE TO HIGH CONCENTRATIONS: Feeling of weakness, irritation of the respiratory tract, nausea, vomiting, headache, central nervous system depression, dizziness, narcosis, excited/restless, drunkenness, disturbed motor response, respiratory difficulties, disturbances of concentration.

ACETONE

SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	ACETONE	53 ASSEMBLY DRIVE
Manufacturers Code:	ACE1, ACE5, ACE25	TULLAMARINE VIC 3043
Date:	September 2020	ABN: 40 959 725 049 Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598 Email: gsmart@bigpond.net.au Web: www.quicksmartproducts.com.au

Symptoms/Injuries after Skin Contact	ON CONTINUOUS EXPOSURE/CONTACT: Dry skin, cracking of the skin.
Symptoms/Injuries after Ingestion	Dry/sore throat. Risk of aspiration pneumonia. Symptoms similar to those listed under inhalation. AFTER ABSORPTION OF HIGH QUANTITIES: Irritation of the gastric/intestinal mucosa. Change in the haemogramme/blood composition. Change in urine output. Affection of renal tissue. Enlargement/affection of the liver.
Symptoms/Injuries after Intravenous Administration	Not available.
Chronic Symptoms	ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin, skin rash/inflammation, dry/sore throat, nausea, feeling of weakness, loss of weight, possible inflammation of the respiratory tract.

12. ECOLOGICAL INFORMATION

Eco-toxicity	Not considered to be harmful to fishes, invertebrates or plankton. Inhibits activated sludge and considered harmful to algae.
Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic condition.
Mobility	No (test) data available.
Note	This substance is not considered to be persistent, bio accumulating nor toxic (BT), not very persistent nor bio accumulating. Avoid release to the environment.

13. DISPOSAL CONSIDERATIONS

Disposal Methods	Dispose of waste according to Federal, EPA, State and Local Regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers.
-------------------------	---

14. TRANSPORT INFORMATION

Proper Shipping Name	Acetone
UN number	1090
DG Class	3 Flammable
Subsidiary Risk 1	Non Allocated
Packaging Group	II
Hazchem Code	2YE
Marine Pollutant	No
Special Precautions for User	Refer to incompatibilities in Section 7 and stability and reactivity information in Section 10.
Additional Transport Requirements	Nil

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Chemical Inventory Status	Listed in AICS (AUST), DLS, INV (CN), ENCS (JP), TACA, EINECS, KECI (KR) and PICCS (PH)
----------------------------------	---

ACETONE

SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	ACETONE	53 ASSEMBLY DRIVE
Manufacturers Code:	ACE1, ACE5, ACE25	TULLAMARINE VIC 3043
Date:	September 2020	ABN: 40 959 725 049
		Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598
		Email: gsmart@bigpond.net.au
		Web: www.quicksmartproducts.com.au

16. OTHER INFORMATION

Contact Person/Point Technical Information: (03) 9338 6655

Date of Preparation or last revision of SDS SDS reviewed: 3 September 2020

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
ADG Code	Australian Code for the Transport of Dangerous Goods by Road & Rail
AICS	Australian Inventory of Chemical Substances
CAS Number	Chemical Abstracts Service Registry Number
GHS	Globally Harmonised System of Classification and Labelling
HAZCHEM Code	Emergency action code of numbers and letters which gives information to emergency services
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LEL	Lower Explosion Limit
mg/m³	Milligrams per Cubic Metre
NOHSC	National Occupational Health and Safety Commission
ppm	Parts Per Million
STEL	Short Term Exposure Limit
SDS	Safety Data Sheet
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
TWA	Time Weighted Average
UEL	Upper Explosion Limit

This SDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user must review this SDS in the context of how the product will be handled in the workplace and in conjunction with other materials. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material or from any failure to adhere to recommendations. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company.

END OF SDS