



**INTRODUCING QUICK SMART LUBRICANTS, A SMALL NICHE
MARKET SPECIALITY COMPANY CATERING FOR YOUR INDUSTRIAL OIL
REQUIREMENTS**

HYDRAULIC OILS

DESCRIPTION Quick Smart Hydraulic Oils are quality oils and have various applications as circulating and bearing oils, also gear oil. The range incorporates rust, corrosion, oxidation and foam inhibitors along with anti-wear additives and demulsifiers.

ISO Viscosity Grades available : 22, 32, 46, 68, 100, 150

APPLICATION Recommended for the lubrication of a wide range of equipment where high rust and oxidation resistance, anti-wear properties, foam resistance and excellent demulsibility are required.

Hydraulics

Particularly suited to all types of hydraulic systems and pumps, operating at high or low temperatures, pressures or speeds.

Grades 32 & 68 are popular in earth moving hydraulics. Specifically recommended for use in the hydraulic systems of mobile and stationary plant.

Gears

May be used in lightly loaded gear boxes containing spur, helical, double helical and straight bevel gearing. NOT recommended for spiral bevel, hypoid and worm gears or where EP gear lubricants are called for.

Bearings

Suitable for ball and roller bearings and plain bearings. When selecting a viscosity grade to suit the bearing size, temperature of operation and speed of rotation, the manufacturers' recommendations should be adhered to.

Compressors

Suitable for most types of compressors, particularly reciprocating compressors.

Others

Widely used as turbine oils and in factory circulating systems. Also suitable for fluid couplings and transmission chains operating in oil tight castings.

PRODUCT BENEFITS

- Premium quality hydraulic oils which are used as multipurpose lubricants suitable for a wide range of industrial equipment.
- Offer excellent wear and corrosion protection, foam resistance and oxidation stability.
- Have good demulsibility leading to longer service life.



**INTRODUCING QUICK SMART LUBRICANTS, A SMALL NICHE
MARKET SPECIALITY COMPANY CATERING FOR YOUR INDUSTRIAL OIL
REQUIREMENTS**

HYDRAULIC OILS

PRODUCT	CODE	SIZE	CTN QTY
HYDRAULIC OIL ISO22	HYD22-1	1LTR	12
	HYD22-5	5LTR	4
	HYD22-20	20LTR	1
	HYD22-205	205LTR	1
HYDRAULIC OIL ISO32	HYD32-1	1LTR	12
	HYD32-5	5LTR	4
	HYD32-20	20LTR	1
	HYD32-205	205LTR	1
HYDRAULIC OIL ISO46	HYD46-1	1LTR	12
	HYD46-5	5LTR	4
	HYD46-20	20LTR	1
	HYD46-205	205LTR	1
HYDRAULIC OIL ISO68	HYD68-1	1LTR	12
	HYD68-5	5LTR	4
	HYD68-20	20LTR	1
	HYD68-205	205LTR	1
HYDRAULIC OIL ISO100	HYD100-1	1LTR	12
	HYD100-5	5LTR	4
	HYD100-20	20LTR	1
	HYD100-205	205LTR	1
HYDRAULIC OIL ISO 150	HYD150-1	1LTR	12
	HYD150-5	5LTR	5
	HYD150-20	20LTR	1
	HYD150-205	205LTR	1