Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80W-140 Synthetic Gear Lubricant

(30536330/SDS_GEN_AU/EN)

Date of print 18.09.23



Safety data sheet

Page: 1/9

Quick Smart Products Safety data sheet

Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80w-140 Synthetic Gear Lubricant

(30536330/SDS GEN AU/EN)

Date of print 18.09.23

1. Substance/preparation and manufacturer/supplier identification

Roadtrans 80W-140 Synthetic Gear Lubricant

Other Names: Emgard® EP80w-140

Use: Universal axle fluid, lubricants

Supplier:

Quick Smart Products Pty Ltd (ABN: 40 959 725 049)

53 Assembly Drive Tullamarine

Victoria 3043

Telephone: 03 9933 6933 Fax: +6 13 93352699

Manufacturer:


BASF Australia Limited (ABN 62 008 437 867) Level 12, 28 Freshwater Place Southbank Victoria 3006, AUSTRALIA

Telephone: +61 3 8855-6600 Telefax number: +61 3 8855-6511

Emergency information:

2. Hazard identification

BASF Emergency Advice Number: 1800 803 440 (24h) [within Australia] BASF Emergency Advice Number: + 61 3 8855 6666 [outside Australia]



Hazardous to the aquatic environment - acute: Cat. 3 Hazardous to the aquatic environment - chronic: Cat. 3





Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80W-140 Synthetic Gear Lubricant

(30536330/SDS_GEN_AU/EN)

Date of print 18.09.23

Label elements and precautionary statement:

Hazard Statement:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

Avoid release to the environment.

Precautionary Statements (Disposal):

Dispose of contents/container to hazardous or special waste collection point.

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

May produce an allergic reaction. Contains: N-1-NAPHTHYLANILINE, Polysulfides, di-tert-Bu

3. Composition/information on ingredients

Chemical nature

Lubricant preparation

Hazardous ingredients

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)

Content (W/W): >= 0.3 % - < 3 % Flam. Liq.: Cat. 3

Acute Tox.: Cat. 4 (oral) Eye Dam./Irrit.: Cat. 1 Skin Sens.: Cat. 1 Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

Polysulfides, di-tert-butyl

Content (W/W): < 5 % Skin Sens.: Cat. 1B CAS Number: 68937-96-2 Aquatic Acute: Cat. 3 Aquatic Chronic: Cat. 3

N-1-Naphthylaniline

Content (W/W): >= 0.3 % - < 1 % Acute Tox.: Cat. 4 (oral) CAS Number: 90-30-2 Skin Sens.: Cat. 1B

STOT RE (Spleen, Kidney): Cat. 2

Aquatic Acute: Cat. 1
Aquatic Chronic: Cat. 1
M-factor acute: 1
M-factor chronic: 1

4. First-Aid Measures

General advice:

Remove contaminated clothing.

Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80W-140 Synthetic Gear Lubricant

(30536330/SDS_GEN_AU/EN)

Date of print 18.09.23

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water.

On contact with eves:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:

Rinse mouth and then drink plenty of water.

Note to physician:

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Further important symptoms and effects are so far not known.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media: water spray, dry powder, foam

Unsuitable extinguishing media for safety reasons:

water jet

Specific hazards:

harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

Use personal protective clothing. Breathing protection required.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80W-140 Synthetic Gear Lubricant

(30536330/SDS GEN AU/EN)

Date of print 18.09.23

7. Handling and Storage

Handling

No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

8. Exposure controls and personal protection

Components with occupational exposure limits

No occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Suitable respiratory protection for higher concentrations or long-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374):

nitrile rubber (NBR) - 0.4 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Hands and/or face should be washed before breaks and at the end of the shift.

Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80W-140 Synthetic Gear Lubricant

(30536330/SDS_GEN_AU/EN)

Date of print 18.09.23

9. Physical and Chemical Properties

Form: liquid
Colour: amber
Odour: characteristic

Odour threshold: No applicable information available.

pH value: insoluble

Melting point: -15 °C

Boiling point: not determined

Flash point: \Rightarrow 180.00 °C (ASTM D92)

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor

pressure.

Flammability (solid/gas): not flammable

Lower explosion limit:

For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15

°C below the flash point.

Upper explosion limit: For liquids not relevant for

classification and labelling.

Ignition temperature: not determined

Thermal decomposition: No decomposition if stored and

handled as prescribed/indicated.

Self-heating ability: It is not a substance capable of

spontaneous heating.

Explosion hazard: not explosive
Fire promoting properties: not fire-propagating

Vapour pressure: The product has not been tested.

Density: 0.897 g/cm3

(15.6 °C) 0.895 g/cm3 (20 °C)

Solubility in water: insoluble

Hygroscopy: Non-hygroscopic

Partitioning coefficient n-octanol/water (log Pow):

Study scientifically not justified.

Viscosity, dynamic: > 150,000.00 mPa*s

(-26.0 °C)

Viscosity, kinematic: 28.00 - 32.00 mm2/s (ASTM D445)

(100 °C)

Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80W-140 Synthetic Gear Lubricant

(30536330/SDS_GEN_AU/EN)

Date of print 18.09.23

Other Information:

If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Conditions to avoid:

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Thermal decomposition: No decomposition if stored and handled as

prescribed/indicated.

Substances to avoid:

strong oxidizing agents, strong bases, strong acids

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:

No hazardous reactions when stored and handled according to instructions.

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion.

Experimental/calculated data: LD50 rat (oral): > 2,000 mg/kg

Irritation

Experimental/calculated data:

Skin corrosion/irritation rabbit: non-irritant

Serious eye damage/irritation rabbit: non-irritant

Respiratory/Skin sensitization

Assessment of sensitization:

A sensitizing effect on particularly sensitive individuals cannot be excluded.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity

Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80W-140 Synthetic Gear Lubricant

(30536330/SDS_GEN_AU/EN)

Date of print 18/09/23

Assessment of carcinogenicity:

The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

None known

Other relevant toxicity information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

12. Ecological Information

Ecotoxicity

Toxicity to fish:

LC50 > 10 - 100 mg/l

Microorganisms/Effect on activated sludge:

EC0 > 100 mg/l

Mobility

Assessment transport between environmental compartments:

No data available.

Persistence and degradability

Assessment biodegradation and elimination (H2O):

Not readily biodegradable (by OECD criteria).

Bioaccumulation potential

Assessment bioaccumulation potential:

Discharge into the environment must be avoided.

Additional information

Add. remarks environment. fate & pathway:

At the present state of knowledge, no negative ecological effects are expected.

Other ecotoxicological advice:

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80W-140 Synthetic Gear Lubricant

(30536330/SDS_GEN_AU/EN)

Date of print 18/09/23

13. Disposal Considerations

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:

Uncontaminated packaging can be re-used.

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport Information

Domestic transport:

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): Not Scheduled

Registration status:

AICS, AU Import under LVE blocked / not listed

Page: 9/9

Quick Smart Products Safety data sheet

Date / Revised: 18.09.23 Version: 3.0

Product: Roadtrans 80W-140 Synthetic Gear Lubricant

(30536330/SDS_GEN_AU/EN)

Date of print 18/09/23

16. Other Information

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor a technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed

ABN: 61 005 625 025 www.quicksmartproducts.com.au Phone: +61 3 9398 4444 Email: sales@advancechemicals.com.au