



QUICK SMART PRODUCTS PTY LTD
53 Assembly Drive
Tullamarine Vic 3043
ABN: 40 959 725 049

Ph: 03 9338 6655 Fax: 03 9335 2598
Email: qsmart@bigpond.net.au
Website: www.quicksmartproducts.com.au

Technical Data Sheet

Surefilm GWS20 Graphite Fluid

Anti-Seize/Lubricant Fluid

Hot Forging Die Lubricant

Description

GWS20 Fluid has been designed to provide a uniform chemically inert film of dry lubricant in situations where heat is extreme and a definite fire risk exists as found in steelworks, foundry brick and tile, cement, metal working, tubemakers and other associated industries.

Application

GWS20 Fluid is suitable for treatment of dyes, kiln tyres and support runners, furnace sliding gates and guides, hot drawing and extrusions.

GWS20 Fluid can operate successfully in elevated temperatures up to 600°C.

GWS20 Fluid is generally used neat but can be diluted with water, depending on the application, and still maintain excellent lubricating and coolant properties and the mixture is non-corrosive to most surfaces.

GWS20 Fluid is a stable thixotropic fluid completely non-flammable, non-fuming, having good heat and electric conduction characteristics.

Features

- Friction reducer – solid, premium quality crystalline graphite powder.
- Aqueous medium.
- Non-flammable.
- Non-hazardous.
- No job sticking.

- Improved surface finish.
- Die life improvement.
- Economical.
- Contains superior quality graphite.
- Very effective for heavy press forging operations.

Directions:

Apply by brush, dipping or spray.

Properties

Appearance	:	Black liquid
Flashpoint	:	Product does not support combustion
pH:	:	6 to 8 [Conc. (% w/w): 100%]
Solubility	:	Easily soluble in the following materials: cold water and hot water

Safety Directions

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

If contacted on broken skin, wash with water and seek medical advice if irritation persists.

For cautionary and first aid information, consult the Material Safety Data Sheet (MSDS).